



SUPERFLO

Swimming Pool Filter



The DAYLIFF Superflo range of swimming pool filters are efficient and economical products suitable for domestic pool applications. Three models are available offering the following features:-

- Roto moulded corrosion proof polythelene plastic construction for long life.
- Simple to operate side mounted six position multi-port control valve.
- Screwed top cover for easy access to the filter media.
- Carefully designed internal collector piping giving superior flow performance.
- High grade Dayliff silicon sand media for exceptional filtration efficiency.

Dayliff Superflo filters are tried and tested over many thousands of installations and have proved to provide reliable and effective pool filtration. With a DAYLIFF Superflo filter sparkling clear water is assured at all times.

OPERATING PARAMETERS

Model	Rated Flow (m ³ /hr)	Pump Options		Pool Capacity (Litres)			Recommended Piping Size		Filter Area (m ²)	Dimensions (mm)		MPV Valve Size	Max Pressure (bar)	Weights (kg)		
		Quality	kW	Light Use	Normal Use	Heavy Use	Suction	Delivery		H	D			Media	Nett	Gross*
Superflo Q120	10	QP3	0.6	100,000	80,000	60,000	1½"	1½"	0.24	560	560	1½"	1.1	120	13	155
Superflo Q160	12	QP4	0.75	120,000	96,000	72,000	2"	1½"	0.3	720	630	1½"	1.2	160	19	229
Superflo Q200	15	QP6	1.1	150,000	120,000	90,000	2"	2"	0.39	710	710	1½"	1.2	200	22	296

* Includes media and water

